
PRODUCT DESCRIPTION

4075RLA® Conform Series® application tape is standard weight saturated paper coated with a high tack rubber adhesive designed specifically as a premasking of small and mid-sized die cut or prespaced vinyl and printed graphics. 4075RLA® features RLA® technology with improved adhesion to paper or film release liners.

Adhesive	Rubber-based
Color	White/Translucent
Caliper, facestock	100-113 microns (4.0 - 4.5 mils)
Caliper, facestock + adhesive	125-138 microns (5.0 - 5.5 mils)
Adhesion to Stainless Steel	18 – 20 N/100mm (16 – 18 oz.)
Tensile	297 N/100mm (17lb./in)
Elongation	3-4%
Tear Resistance (grams)	50
Shelf life Stored at 22°C (72°F)/ 50-55 % RH	1 year

FEATURES & BENEFITS

- Removes easily following graphics application.
- If adhesive touches adhesive, Conform pulls apart easily with no adhesive delamination.
- Works well in either wet or dry applications with no adhesive transfer.
- Available in factory-cut rolls with no damaged edges for trouble-free unwind.

APPLICATIONS

- Premask for small and medium size vinyl graphics .
- All-purpose application tape for wet and dry applications.
- Excellent for transferring graphics to banners.

Important Notice: All R Tape products are subject to continuous quality control throughout the manufacturing process and are warranted to be free from manufacturing defects. R Tape stands behind its products and will replace or credit any defective material. Because R Tape products are used for a variety of applications, the purchaser is responsible for determining the suitability and performance of this product for their specific purpose, prior to use and the purchaser shall assume all risks regarding such use.

RTape Corp.
6 Ingersoll Road, South Plainfield, NJ 07080
908-753-5570 Fax 908-753-5014 800-440-1250
E-mail: sales@rtape.com
www.rtape.com

Represented in Europe by:
Industrial Consultants
Industriezone Langevoorde, Groendreef 35
9880 Aalter, Belgium
Tel: 32 9 216 67 00 Fax: 32 9 216 67 09
sales@rtape.be