

# Glo-Bright Printable Photoluminescent

## product specification

Glo-Bright Printable Photoluminescent is a flexible Class B safety grade self-adhesive Photo Luminescent Vinyl that meets the most rigorous standards for indoor safety applications.

Thickness	ACRYLIC (SOLVENT BASED)
-----------	-------------------------

Peel adhesion to:	
Stainless steel	80 N/100 mm
Powder coated surfaces *	80 N/100 mm
Polyethylene	60 N/100 mm

Shear Adhesion to:	
Stainless Steel 1Kg 12.5sqmm	80 N/100 mm
Tack	80 N/100 mm
Luminous Values	60 N/100 mm
Service Temperature (High)	Not recommended above 65°C max. service
Service Temperature (Low)	Not recommended below -40°C

## suitability

Powered by absorbed ambient light, this is the latest generation of Photo Luminescent Vinyl and contains pigments that produce a brighter afterglow in blackout or low light environments.

Engineered to exceed requirements for emergency exits and fire safety signage in buildings, marine, rail and military applications.

## material characteristics

High level of luminance

Permanent adhesive

Satin print receptive finish

Quick drying: Faster drying improves production rates and efficiency

Excellent layflat characteristics makes working with Glo-Brite® 7535 easy

INK COMPATIBILITY:

Eco-solvent, solvent and UV Ink

Version 1 12/01/2023